



*Specifications subject to change without notice.

[NEO6-618SUD Feature]

- Tokiwa NEO series is high end machine series. It has the best performance and machine specifications. It is able to operated without manual by its microcomputer.
- This machine is able to do automatic wrapping with printed film. Also, it can cost down with non-printed film.
- Its safety and operation are improved during setup with individual stop switch to stop Endsealer as a pre-installed option.

[NEO6-618SUD SPEC]

Product to be Wrapped	Aerosol Can, Bowl Noodles, etc.
Wrapping Speed	max 300 packs/min (it depends on kind of products and material)
Cut Pitch	130mm - 600mm
Power Consumption	3 Phase, 200V, 5.5kw (Additional power for shrinktunnel is required)

The Best Selection
for Bowl Nooble
shrink wrapping.



[Optional Items]

- **One Touch Detachable Scrap Film Winder.**
Paper coreless Scrap Film Winder realize only scrap film part can be detached from it for recycling. (No paper core required) At one touch, scrap film can be detached as same As its naming
- **Belt Divided Autofeeder.**
Star Wheel Autofeeder, Timing Screw Divider.
- **Automatic Film Splicer.**
When detects the end of film activates splice to next film roll.
Splice by heat seal. Splice by double faced adhesive tape.
- **Static Electricity Sealer.(For only Longseal)**
No scrap film is made and reduce running cost 1/18 of heat sealer with less electric and film consumption.

- **Web Guiding Systems.**
It minimize web position errors to keep center position of the film to have stable long Seal. Using together with Automatic Film Splicer, ensure higher productivity.
- **Flex Length Conveyor.**
Smooth product transfer from tubing conveyor to discharge conveyor realized. Two conveyor' s edge contacts when product transfer with less vibration. Suitable for multi package and small product.