



*Specifications subject to change without notice.

【Feature】

- With half machine length (compare to other Tokiwa wrappers), it is able to be installed in limited space.
- Excellent operation by standard 12 inch large sized color touch panel.
- 99 items installable.
- Easy to move its location by caster wheel and socket type power cable.
- Automatic feeding system can be added after machine installation.
- Paper core less one touch release type scrap winder.
- All film holders are designed to locate at lower position for easy film roll replacement.
- Height of Endsealer position is adjustable.



*Image Illustration

【Options】

- Automatic Infeed System
- Automatic Perforation Device
- Labeling Machine
- Date Coder
- Static Electricity Sealer (For Only Longseal)

【SPEC】

Example product to be wrapped	Pump Bottles, Tubes, Each Type of Containers
Wrapping speed	MAX 50packs / min. (depend on items and material)
Cut pitch	90 ~ 470mm
Power consumption	3phase, 200V, 4.5kW (without shrink tunnel)
Tunnel Length	Total length 800mm (as standard 30packs / min)
Maximum film width	450mm

TOKIWA KOGYO CO., LTD.

<http://www.tokiwrap.co.jp>

Head office and main factory

2-190-9 Yamada Nishi-ku
Sakai-shi Osaka Japan

Phone +81-72-273-1234
Fax +81-72-273-8300

Branch and factory

2-2-18 Shiratori,
Katsushika-ku, Tokyo
125-0063 Japan

Phone +81-3-3603-3271
Fax +81-3-3690-3997

Sales Office

Kyushu : Hakata-eki
Higashiguchi Bldg. 7th floor,
1-11-15 Hakata-eki Higashi,
Hakata-ku, Fukuoka-shi
Phone +81-92-451-1428
Fax +81-92-451-1429